



Oilmaster® Bottom Loading Hose

Type GGB901

Applications: This type is designed exclusively for the bottom loading arm application for filling tank trucks suitable for all grades and blends of refined gasoline products with unique fiberglass flame resistant layer.

Construction:

- Color/Cover: Black with a blue and white stripe/PVC coated Nylon, Abrasion, UV and Ozone resistant
- Inner Wire: Galvanized Steel
- Inner lining: High Density Polypropylene
- Carcass: Fiberglass Flame-Resistant layer, Polypropylene fabrics and Nylon films
- Outer Wire: Galvanized Steel

Physical properties:

- Temperature Range: -22°F to +212°F (-30°C to +100°C)
- Maximum elongation: ≤10% on test pressure
- Vacuum range: 26 inHg (660 mmHg), 0.9 bar
- Electrical properties: Electrically Conductive
≤1.0 ohm/m

Standards: BS5842, NAHAD-600:2005

End Fittings: Specially designed end fittings have been developed for use with United Flexible composite hoses that have a unique leak-proof sealing face and specially machined helical spiral shank which engages into the corresponding internal helix wire when secured into the hose by either crimping or swaging the external ferrules. See page 22 for more information about end connections.

Lengths: For GGB901 Bottom Loading Hose measure the lengths as either “pressurized” or “empty”. The effect of elongation must be calculated in order to produce the correctly manufactured length and price.

TECHNICAL DATA: TYPE GGB901									
Inside Diameter		Working Pressure		Min. Bend Radius		Approx Weight		Maximum Length	
Inches	mm	PSI	Bar	Inches	mm	lb/ft	kg/m	Feet	Meters
3	80	200	14	9.50	240	2.00	3.00	100	30
4	100	200	14	14.50	360	3.00	4.50	100	30

Pressure based on safety factor 4:1

Dimensions and weight are approximate and are subject to change

For additional technical data such as pressure drop, max. flow rates and tensile strength, please consult United Flexible engineering

Increased operating temperatures will reduce working pressure of the assemblies

Fitting pressure rating may limit or reduce the rated working pressure of the assembly

Rated working pressure is @ 70°F (21°C)